



## Technical Data Sheet

### Model – 8150 & 8151 Spring Loaded Test Leads

This probe is used with Surface Mount and High-Density circuits. The 8 tips included in these kits will insure a positive non-slip connection to any surface.

#### Specifications

- 1000 Volts Rated
- CAT III 1000 V, CAT IV 600 V, 10A
- 18 GA Silicone Leads
- Low Resistance Gold Contacts

#### Features

- All Tips 23K Gold Plated
- Soft Comfortable Handle
- Lengths Available 24", 36", 48"
- Probe Handle Length 5.5"
- Reliable Soldered Connections for Extra Durability.



Needle Tip Spring Type 	Cluster Tip Spring Type 	Cluster Tip Spring Type 	.025" Tip Spring Type 
8162 Needle Tip	8163 Cluster Tip	8164 Cluster Tip	8166 Rounded Tip

#### Material:

Probe Body- Vinyl Tip and soft PVC handle.  
 Probe Tip- Gold Plated Stainless Steel  
 Banana Connector- Nylon Connector with Gold plated 4mm  
 Banana Plug.

**To Replace Probe Tip -Grip gold tip with small needle nose pliers and pull straight out. (Be careful not to damage tip by squeezing to tight)  
 Insert new tip using needle nose pliers.**

Available Meter Connections	Model 8150 (Shown) Rt. Angle Banana Plug	Model 8051 Retractable Banana Plug
<b>Ordering information-</b> Model 8150 shown above. Includes 1ea red & black test lead, 2ea tips shown above		