

MFG-2000 Specifications

The specifications apply when the MFG-2000 is powered on for at least 30 minutes under +20°C~+30°C.

	MFG-2000 series specific functions					
	CH1	CH2	25MHz Pulse Generator	RF Generator (Function With ARB)	Power Amplifier	Modulation /Sweep/Burst/ Frequency Counter
	Function With ARB	Function With ARB				
MFG-2110	•10MHz		●			
MFG-2120	•20MHz		●			
MFG-2120MA	•20MHz		●		●	●
MFG-2130M	•30MHz		●			●
MFG-2160MF	•60MHz		●	•160MHz		●
MFG-2160MR	•60MHz		●	•320MHz		●
MFG-2230M	•30MHz	•30MHz	●			●
MFG-2260M	•60MHz	•60MHz	●			●
MFG-2260MFA	•60MHz	•60MHz	●	•160MHz	●	●
MFG-2260MRA	•60MHz	•60MHz	●	•320MHz	●	●

CH1/ CH2

Arbitrary Functions

ARB function	Built-in
Sample Rate	200 MSa/s
Repetition Rate	100MHz
Waveform Length	16k points
Amplitude Resolution	14 bits
Non-Volatile Memory	10sets 16k points(1)
User-defined output section	From point 2~16384
User-defined output marker section	From point 2 ~ 16384
Output mode	1~1048575 cycles or infinite mode

Frequency Characteristics

Range	Sine	60MHz(max)
	Square	25MHz(max)
	Triangle, Ramp	1MHz
Resolution		1μHz
Accuracy Stability	±20 ppm	
Aging	±1 ppm, per 1 year	
Tolerance	≤1μHz	

Output Characteristics(2)

Amplitude Range	1mVpp to 10 Vpp (into 50Ω) 2mVpp to 20 Vpp (open-circuit)
Accuracy	±2% of setting ±1 mVpp (at 1 kHz/into 50Ω without DC offset))
Resolution	0.1mV or 4 digits
Flatness	± 1% (0.1dB) ≤1MHz ± 3% (0.3dB) ≤50 MHz ± 10% (0.9dB) ≤160MHz ± 30% (3dB) ≤320MHz (sinewave relative to 1 kHz/into 50Ω)
Units	Vpp, Vrms, dBm

Offset Range

±5 Vpk AC +DC (into 50Ω)

±10Vpk AC +DC (Open circuit)

1% of setting + 5mV+ 0.5% of amplitude

Waveform Output	Impedance	50Ω typical (fixed); > 10MΩ (output disabled)
	Protection	Short-circuit protected Overload relay automatically disables main output
	Ground Isolation	42Vpk max
Sync Output	Range	TTL-compatible into >1kΩ
	Impedance	50Ω standard
	Ground Isolation	42Vpk max
Sine wave		
Characteristics(3)		
	Harmonic distortion	-60 dBc DC ~ 200kHz, Ampl>0.1 Vpp -55 dBc 200kHz ~ 1 MHz, Ampl>0.1 Vpp -45 dBc 1MHz ~ 10 MHz, Ampl > 0.1Vpp -30 dBc 10MHz ~ 320MHz, Ampl > 0.1Vpp
	Total harmonic distortion	< 0.1% (Ampl>1Vpp) DC~100 kHz
Square wave		
Characteristics		
	Rise/Fall Time	<15ns
	Overshoot	<5%
	Asymmetry	1% of period +5 ns
	Variable duty Cycle	0.01% to 99.99%(limited by the current frequency setting)
	Jitter	20ppm+500ps(4)
Ramp Characteristics		
	Linearity	< 0.1% of peak output
	Variable Symmetry	0% to 100%
Pulse Characteristics		
	Frequency	1uHz~25MHz
	Pulse Width	≥ 20nS(limited by the current frequency setting)
	Variable duty Cycle	0.01%~99.99%(limited by the current frequency setting)
	Overshoot	<5%
	Jitter	20ppm +500ps(4)
Pulse Generator		
	Amplitude	1mVpp to 2.5 Vpp (into 50Ω) 2mVpp to 5 Vpp (open-circuit)
	Offset	±1 Vpk ac +dc (into 50Ω) ±2Vpk ac +dc (Open circuit)
	Frequency	1uHz~25MHz
	Pulse Width	20ns~999.9ks(limited by the current frequency setting)
	Variable duty Cycle	0.01%~99.99%(limited by the current frequency setting)
	Leading and Trailing Edge Time(5)	10ns~ 20s(1ns resolution) (limited by the current frequency and pulse width settings)
	Overshoot	<5%
	Jitter	100ppm +500ps(4)
RF Generator		
Arbitrary Functions	Waveforms	Sine-DDS ,Square ,Ramp ,Pulse ,Noise ,Sine-ARB
	ARB function	Built-in
	Sample Rate	200 MSa/s
	Repetition Rate	100MHz
	Waveform Length	16k points
	Amplitude Resolution	14 bits
	User-defined output section	From point 2~16384
	Jitter	20ppm +5ns
Frequency Characteristics		

Range	Sine	1uHz~160MHz(MFG-2XXXMF) 1uHz~320MHz(MFG-2XXXMR)
	Square	25MHz(max)
	Triangle, Ramp	1MHz
Resolution		1μHz
Accuracy Stability	±20 ppm	
Aging	±1 ppm, per 1 year	
Tolerance	≤1μHz	

Output Characteristics(2)

Amplitude(into 50Ω)	1mVpp to 2 Vpp 1mVpp to 1 Vpp	(MFG-2XXXMF) (MFG-2XXXMR)
Accuracy	±2% of setting ±1 mVpp (at 1 kHz/into 50Ω without DC offset))	
Resolution	0.1mV or 4 digits	
Flatness	± 1% (0.1dB) ≤1MHz ± 3% (0.3dB) ≤50 MHz ± 10% (0.9dB) ≤160MHz ± 30% (3dB) ≤320MHz (sinewave relative to 1 kHz/into 50Ω)	
Offset	±1 Vpk AC +DC (into 50Ω) ±2Vpk AC +DC (Open circuit)	
Waveform Output	Impedance	50Ω typical (fixed) > 10MΩ (output disabled)
Sine wave Characteristics(3)		
Harmonic distortion	-60 dBc -55 dBc -45 dBc -30 dBc	DC ~ 200kHz, Ampl>0.1 Vpp 200kHz ~ 1 MHz, Ampl>0.1 Vpp 1MHz ~ 10 MHz, Ampl > 0.1Vpp 10MHz ~ 320MHz, Ampl > 0.1Vpp
Total harmonic distortion		< 0.1% (Ampl>1Vpp) DC~100 kHz

Square wave Characteristics

Rise/Fall Time	<15ns
Overshoot	<5%
Asymmetry	1% of period +5 ns
Variable duty Cycle	0.01% to 99.99%(limited by the current frequency setting)
Jitter	20ppm+500ps(4)

Ramp Characteristics

Linearity	< 0.1% of peak output
Variable Symmetry	0% to 100%

Modulation/Sweep

Modulation Type	AM,FM,PM,FSK,PWM (The detail same as CH1 modulation specification)
Sweep type	Frequency
Source	INT/EXT (INT only for AM,FM,PM, PWM)

PSK

Carrier Waveforms	Sine, Square, Triangle, Ramp, Pulse
Modulating Waveforms	50% duty cycle square
Internal Frequency	2 mHz to 1 MHz
Phase Range	0°~360.0°
Source	Internal / External

ASK

Carrier Waveforms	Sine, Square, Triangle, Ramp, Pulse
Modulating Waveforms	50% duty cycle square
Internal Frequency	2 mHz to 1 MHz

	Amplitude Range	0%~100.0%
	Source	Internal / External
Power Amplifier		
	Input Impedance	10KΩ
	Input voltage	1.25Vpmax
	Working Mode	Constant Voltage
	Gain	20dB
	Output Power (RL=8Ω)	20W(Square)
	Output Voltage	12.5Vpmax
	Output Current	1.6Amax
	Rise/Fall Time	<2.5uS
	Full Power Bandwidth	DC-100KHz
	Overshoot	5%
	Total harmonic distortion	< 0.1% (Ampl>1Vpp) 20Hz~20 kHz
	Ground Isolation	42Vpk max
Advanced Functions		
AM Modulation		
	Carrier Waveforms	Sine, Square, Triangle, Ramp, Pulse, Arb
	Modulating Waveforms	Sine, Square, Triangle, Upramp, Dnramp
	Modulating Frequency	2mHz to 20kHz (Int) DC to 20kHz (Ext)
	Depth	0% to 120.0%
	Source	Internal / External
FM Modulation		
	Carrier Waveforms	Sine, Square, Triangle, Ramp
	Modulating Waveforms	Sine, Square, Triangle, Upramp, Dnramp
	Modulating Frequency	2mHz to 20kHz (Int) DC to 20kHz (Ext)
	Peak Deviation	DC to max frequency
	Source	Internal / External
PM		
	Carrier Waveforms	Sine, Square, Triangle, Ramp
	Modulating Waveforms	Sine, Square, Triangle, Upramp, Dnramp
	Modulation Frequency	2mHz to 20kHz (Int) DC to 20kHz (Ext)
	Phase deviation	0°~360.0°
	Source	Internal / External
SUM		
	Carrier Waveforms	Sine, Square, Triangle, Ramp
	Modulating Waveforms	Sine, Square, Triangle, Upramp, Dnramp
	Modulation Frequency	2mHz to 20kHz (Int) DC to 20kHz (Ext)
	SUM depth	0%~100.0%
	Source	Internal / External
PWM		
	Carrier Waveforms	Sine, Square, Triangle, Ramp
	Modulating Waveforms	Sine, Square, Triangle, Upramp, Dnramp
	Modulation Frequency	2mHz to 20kHz (Int) DC to 20kHz (Ext)
	Phase deviation	0%~100.0% pulse width
	Source	Internal / External
FSK		
	Carrier Waveforms	Sine, Square, Triangle, Ramp, Pulse
	Modulating Waveforms	50% duty cycle square
	Internal Frequency	2 mHz to 1 MHz
	Frequency Range	1μHz to max frequency

	Source	Internal / External
Sweep	Waveforms	Sine, Square, Triangle, Ramp
	Type	Linear or Logarithmic
	Sweep direction	Sweep up or sweep down
	Start/Stop Freq	1uHz to max frequency
	Sweep Time	1ms to 500s
	Source	Internal / External
	Trigger	Single, External, Internal.
	Marker	Marker signal on falling edge (programmable)
	Source	Internal / External
Burst	Waveforms	Sine, Square, Triangle, Ramp
	Frequency	1uHz~Max Frequency
	Pulse count	1~1000000 Cycles or infinite
	Start/ Stop Phase	-360.0°~+360.0°
	Internal Frequency	1 us~500 s
	Gate source	External Trigger
	Trigger Source	Single, External, Internal.
	Trigger Delay	NCycle, Infinite
External Trigger Input	0s~100 s	
	Type	For FSK, Burst, Sweep
	Input Level	TTL Compatibility
	Slope	Rising or Falling(Selectable)
	Pulse Width	>100ns
External Modulation Input	Input Impedance	10kΩ · DC coupled
	Type	For AM, FM, PM,SUM,PWM
	Voltage Range	±5V full scale
	Input Impedance	10kΩ
	Frequency	DC to 20kHz
Trigger Output	Ground Isolation	42Vpk max
	Type	For FSK,Burst, Sweep
	Level	TTL Compatible into 50Ω
	Pulse Width	>450ns
	Maximum Rate	1MHz
Frequency Counter	Fan-out	≥4 TTL Load
	Impedance	50Ω Typical
	Range	5Hz to 150MHz
	Accuracy	Time Base accuracy±1count
	Time Base	±20ppm (23°C ±5°C)
	Resolution	The maximum resolution is: 100nHz for 1Hz, 0.1Hz for 100MHz.
	Input Impedance	1kΩ/1pf
	Sensitivity	35mVrms ~ 30Vms (5Hz to 150MHz)
	Ground Isolation	42Vpk max
	Dual Channel Function(CH1/CH2)	
	Phase	-180° ~180°
		Synchronize phase
	Track	CH2=CH1
	Coupling	Frequency(Ratio or Difference)
		Amplitude & DC Offset
Save/Recall	Dsolink	v
		10 Groups of Setting Memories

Interface	LAN(MFG-22XX only), USB
Display	4.3" TFT LCD 480 × 3 (RGB) × 272
General Specifications	
Power Source	AC100~240V, 50~60Hz or AC100~120V, AC220~240V, 50~60Hz
Power Consumption	30W or 80W(With power amplifier)
Operating Environment	Temperature to satisfy the specification : 18 ~ 28°C Operating temperature : 0 ~ 40°C Relative Humidity: ≤ 80%, 0 ~ 40°C ≤ 70%, 35 ~ 40°C Installation category : CAT II
Operating Altitude	2000 Meters
Pollution Degree	IEC 61010 degree 2, Indoor use
Storage Temperature	-10~70°C, Humidity: ≤70%
Dimensions (WxHxD)	266(W) x 107(H) x 293(D) mm
Weight	Approx. 2.5kg
Safety designed to	EN61010-1
Accessories	GTL-101× 1(MFG-21XX) GTL-101× 2(MFG-22XX) Quick Start Guide ×1 CD (user manual + software) ×1 Power cord×1

- (1). A total of ten waveforms can be stored. (Every waveform can be composed of a maximum of 16k points.)
- (2). Add 1/10th of output amplitude and offset specification per °C for operation outside of 0°C to 28°C range (1-year specification).
- (3). DC offset set to zero,
- (4). Jitter specification for RF Generator: 20ppm +5ns.
- (5). Only Pulse channel support